

HEMTEK ST



To the product



Technical data

Article	157.860; 157.861; 157.862; 157.866; 157.867; 157.868; 157.869; 157.870; 157.871	
Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1800-3450 W	
Speed	0.8-12 m/min	2.62-39.37 ft/min
Temperature	100-650 °C	212-1202 °F
Air volume adjustable	Yes	
Welding nozzle / seam width	20-40 mm	0.78-1.57 in
Length	433 mm	17.04 in
Width	350 mm	13.77 in
Height	600 mm	23.62 in
Weight	27 kg	59.52 lb
Plug	CEE blue, 3 poles, 16A; EU, 3 poles, 16A; US, 3 poles, 15A	
Power cable length	3 m	9.84 ft
Approvals	CB Certification; CE	
Protection class	I	
Country of origin	Switzerland	

Scope of delivery

Adjustable hem and piping guide; Rubber plug



HEMTEK ST

Product items

157.860	HEMTEK ST, 230V/3450W, 40mm, EU plug
157.861	HEMTEK ST, 230V/3450W, 30mm, EU plug
157.862	HEMTEK ST, 230V/2350W, 20mm, EU plug
157.866	HEMTEK ST, 230V/3450W, 40mm, CEE 3/16
157.867	HEMTEK ST, 230V/3450W, 30mm, CEE 3/16
157.868	HEMTEK ST, 230V/2350W, 20mm, CEE 3/16
157.869	HEMTEK ST, 120V/1800W, 40mm, US plug
157.870	HEMTEK ST, 120V/1800W, 30mm, US plug
157.871	HEMTEK ST, 120V/1800W, 20mm, US plug